

SANFLEX 2m

Dimension	Unit	Unit/Box
Debljina 6mm		
012-06/2m Sanflex	M	560
015-06/2m Sanflex	M	440
018-06/2m Sanflex	M	400
020-06/2m Sanflex	M	340
022-06/2m Sanflex	M	320
025-06/2m Sanflex	M	290
028-06/2m Sanflex	M	250
032-06/2m Sanflex	M	210
035-06/2m Sanflex	M	180
042-06/2m Sanflex	M	150
Debljina 9mm		
012-09/2m Sanflex	M	456
015-09/2m Sanflex	M	380
018-09/2m Sanflex	M	330
020-09/2m Sanflex	M	250
022-09/2m Sanflex	M	250
025-09/2m Sanflex	M	190
028-09/2m Sanflex	M	190
032-09/2m Sanflex	M	150
035-09/2m Sanflex	M	150
042-09/2m Sanflex	M	110
048-09/2m Sanflex	M	90
054-09/2m Sanflex	M	70
060-09/2m Sanflex	M	66
063-09/2m Sanflex	M	66
076-09/2m Sanflex	M	66
Debljina 13mm		
015-13/2m Sanflex	M	256
018-13/2m Sanflex	M	220
022-13/2m Sanflex	M	180
028-13/2m Sanflex	M	140
035-13/2m Sanflex	M	120
042-13/2m Sanflex	M	90
048-13/2m Sanflex	M	70
060-13/2m Sanflex	M	48
063-13/2m Sanflex	M	48
76-13/2m Sanflex	M	40

SANFLEX STABIL 2m

Dimension	Unit	Unit/Box
Debljina 6mm		
015-06/2m Sanflex Stabil	M	440
018-06/2m Sanflex Stabil	M	400
022-06/2m Sanflex Stabil	M	320
028-06/2m Sanflex Stabil	M	250
035-06/2m Sanflex Stabil	M	180

SANFLEX STABIL 10m

Dimension	Unit	Unit/Box
Debljina 6mm		
015-06/10m B1 Sanflex Stabil	M	300
018-06/10m B1 Sanflex Stabil	M	270
022-06/10m B1 Sanflex Stabil	M	250
028-06/10m B1 Sanflex Stabil	M	220
035-06/10m B1 Sanflex Stabil	M	180



DISTRIBUTER:

Valmaks tim doo
Vodovodska 164e
11000 Beograd, Srbija
Tel.: +381 11 2570 301
E-Mail: office@valmaks.rs

nmc Polska Sp. z o.o.
Ul. Pyskowicka 15,
41-807 Zabrze – Polska
Tel.: +48 32 373 24 40
E-Mail: biuro@nmc.pl



Insulation technologies

SANFLEX



Cevna izolacija od polietilenske ispunjene pene namenjena za izolovanje instalacija grejanja i vodovoda. Niska termička provodljivost smanjuje toplotne gubitke i povećava efikasnost troškova.

SANFLEX izolacija takodje obezbedjuje dobru zvučnu absorpciju.

Technical data

Termička provodljivost (W/m2K)	$\lambda=0,038$ at 16°C
	$\lambda=0,040$ at 40°C
	$\lambda=0,049$ at 75°C
Opseg temperature	0°C - 100°C
Protivpožarna klasa	Euroclass E
Nivo buke (smanjenje)	23dB(A)
Dužina	2m komad

SANFLEX STABIL 2m



Cevna izolacija od polietilenske ispunjene pene namenjena za izolovanje instalacija grejanja i vodovoda. Niska termička provodljivost smanjuje toplotne gubitke i povećava efikasnost troškova.

SANFLEX Stabil 2m izolacija takodje obezbedjuje dobru zvučnu absorpciju i zaštitu od oštećenja. Izolacija je dostupna u 2 boje: crvena i plava

Technical data

Termička provodljivost (W/m2K)	$\lambda=0,038$ at 16°C
	$\lambda=0,040$ at 40°C
	$\lambda=0,049$ at 75°C
Opseg temperature	0°C - 100°C
Protivpožarna klasa	Euroclass E
Nivo buke (smanjenje)	23dB(A)
Dužina	2m komad

SANFLEX STABIL 10m



Cevna izolacija od polietilenske ispunjene pene namenjena za izolovanje instalacija grejanja i vodovoda. Niska termička provodljivost smanjuje toplotne gubitke i povećava efikasnost troškova.

SANFLEX Stabil 10m izolacija takodje obezbedjuje dobru zvučnu absorpciju i zaštitu od oštećenja. Pakovanja od 10m su veoma praktična i omogućavaju uštedu u prostoru. Izolacija je dostupna u 2 boje: crvena i plava

Technical data

Termička provodljivost (W/m2K)	$\lambda=0,038$ at 16°C
	$\lambda=0,040$ at 40°C
	$\lambda=0,049$ at 75°C
Opseg temperature	0°C - 100°C
Protivpožarna klasa	Euroclass E
Nivo buke (smanjenje)	23dB(A)
Dužina	10m komad